FAX BID REQUEST

BID NUMBER: 16934

STATE OF CONNECTICUT ENVIRONMENTAL PROTECTION 141 SOUTH ST., UNIT D WEST HARTFORD CT 06110-1963 PHONE: 860-723-7601 FAX: 860-953-8581

Vendor:							Ship To: State of Ct D.E.P West Hartford Commerce Center 141 South St. Unit D West Hartford, Ct 06110					
Phone:			Fax:				vvest riaitioiu, Ot 00 i iu					
DATE ISSUED			ISSUED BY Carl L. Chu Purchasing Service Officer II		DATE/TIME BID REQUIRED 1/24/0812:00Noon		DATE WORK REQUIRED		F.O.B.		TERMS	
1/15/08			Please return bid to Fax: 860-953-8581 SEE INSTRUCTIONS BELOW				ASAP		ALL PRICES MUST BE F.O.B. DESTINATION		Net 45 days	
ITEM NO.	DESCRIPTION						UNIT	QU	AN	UNIT PRICE	TOTAL	
1.	State of Ct. D.E.P. Is Seeking Bids For 16.5' Rigid Hull Inflatable Boat /60HP Motor & Matching Trailer Package As Per Specifications.						EA.	1	1			
	Note: F.O.B. All Prices Must Be F.O.B. Destinations As Above.											
										Total	•	
NOTE: DO NOT INCLUDE FEDERAL EXCISE TAXES OR CONNECTICUT SALES TAX, AS THE STATE IS EXEMPT. BIDDER INSTRUCTIONS: PLEASE FAX YOUR QUOTE ON THIS FORM TO (860) 953-8581 AND MAIL FORM WITH ORIGINAL SIGNATURE TO THE ADDRESS IN THE UPPER RIGHT HAND CORNER. ALL PRICES MUST BE F.O.B. DESTINATION AND YOU MUST SIGN THIS FORM. THE STATE RESERVES THE RIGHT TO REJECT IN WHOLE OR IN PART ANY AND ALL BIDS. PLEASE NOTE BID DEADLINE. LATE BIDS WILL NOT BE ACCEPTED. THE UNDERSIGNED BIDDER AFFIRMS AND DECLARES: THAT THIS QUOTATION IS EXECUTED AND SIGNED BY SAID BIDDER WITH FULL KNOWLEDGE AND ACCEPTANCE OF THE PROVISIONS OF FORM SP-19 OF CURRENT ISSUE AND IN EFFECT ON THE DATE OF THIS BID ISSUE. FORM SP-19, ENTITLED STANDARD BID AND CONTRACT TERMS AND CONDITIONS TOGETHER WITH THE COMMODITY SPECIFICATIONS, PROPOSAL SCHEDULE, AND SPECIAL BID AND CONTRACT TERMS ARE MADE A PART OF THIS REQUEST FOR QUOTATION.												
		DATE:	VENDOR FEIN/SSN:		ARE YOU INCORPORATED? YES NO			DELIVERY AS REQ=D ABOVE (UNLESS NOTED HERE)				
SIGNED : PRINTED :			TITLE:		TELEPHONE NO. AND EXTENSION :			SASH D		OUNT: PAY TERI		

SPECIFICATIONS FOR RIGID HULL INFLATABLE BOAT, MOTOR, AND TRAILER

The following specifications are to describe a 16.5' rigid hull inflatable boat with a 60 hp 4-stroke outboard motor and a matching trailer. The unit shall be delivered to the Agency as a complete working unit with all accessories mounted and functional. The vessel shall be the manufacturer's latest production model and meet or exceed any and all USCG, Federal and/or State regulations regarding vessels of this type in force at the time of delivery. The boat, motor, and trailer will be covered by manufacturer's standard warranty. All boats are to include all manufacturers' standard equipment unless further specified.

Vessel

- > 16 -foot length; 6'10" foot beam; rigid hull inflatable all weather boat with a center console
- ➤ Heavy duty fiberglass progressive Deep-V hull
- Rated to carry 2400 or more pounds and at least 10 passengers
- Non-skid decking
- > 2 large flow self bailers, deck drains and below deck floatation
- ➤ At least 4 neoprene hypalon fabric 1880 decitex inflation chambers with interconnecting valves that will allow total vessel inflation from 1 point, but does not allow total vessel deflation from 1 point
- Repair kit with pressure gauge
- Foot pump with hose and fittings to inflate
- > Trim tabs
- ➤ Bilge pump at least 1,500 GPH with an electric switch allowing both automatic and manual operation
- > 4 lifting points with rings
- > Stern and bow towing rings made of stainless steel
- Internal reinforced transom with an aluminum engine mounting plate
- Rubbing strake all around, extra on the bow made of non-marking material
- Lifeline all around on lacing cuffs
- Bow handle
- Manufacturer's standard seating for 3 passengers
- ➤ Heavy Duty standup center console with a windshield.
- Stainless steel grab handles

Engine

- Four stroke, 60 hp, 4 cylinder outboard motor
- > Shaft length to be matched to the transom height requirements of the vessel
- Motor should be mounted with all mounting hardware included
- All steering cables, fuel lines, controls, harnesses and a hydraulic steering system must be included
- To include 2 propellers for general all around use

> To include two 6 gallon plastic fuel tanks with tie down straps.

Electrical and Electronics

- ➤ Deep cycle marine battery with minimum 800 cold cranking amps, 980 marine cranking amps and a 104 minute reserve capacity
- Main disconnect switch for electrical system
- ➤ LED style navigation lights to USCG standards
- ➤ 2 Console mounted 12 volt DC receptacles
- Standard manufacturer's guages

Trailer

The following are the specs for the trailer

- Galvanized finish.
 - > Single axle design with galvanized leaf springs
 - > Should be equipped with rollers and not bunk boards
 - > Hand winch and flat strap
 - > Spare tire and wheel lockable to the trailer
 - > Swing up style tongue jack with wheel on the bottom
 - > Transom straps
 - Wheel hubs are to be equipped with external lubricant (grease) fittings.
 - Coupler to receive a 2" ball
 - Safety chains
 - ➤ LED style lighting (Signal lights, tail lights, brake lights); Trailer lights to be heavy duty, impact resistant, and corrosion resistant, designed for boat trailer use.
 - Manufacturers standard fenders with safety step pad

Miscellaneous

Each vendor will supply the following manuals:

All available repair manuals (CD's are acceptable) All available parts manuals (CD's are acceptable) One operating manual